

JOKE® Basic-Clean

Ultrasonic cleaning devices



JOKE® Basic-Clean

Ultrasonic cleaning devices



The new standard in cleaning

Basic-Clean is the new standard series among the ultrasonic cleaning devices from JOKE®. With their high performance vibration systems and wealth of practical equipment, they offer a high standard at a fair starting price.

All the devices are equipped with cleaning troughs made of cavitation-proof stainless steel and are fitted as standard with run dry-proof ceramic heating. The heating temperature is electronically adjustable and likewise the cleaning time. A specific temperature at which the cleaning process is to begin automatically can be entered with the autostart option. The time and temperature are indicated by LED on the control panel.

"Sweep" and "degas" for optimum effective cleaning; the sweep function now ensures homogeneous and uniform distribution of the vibrations in the cleaning bath, even in our starter models. Degas makes it possible to achieve rapid degassing of the cleaning fluid. Particularly practical on new addition of fluid and even performed fully automatically by auto degas.

Emptying of the devices has also been optimised in the new generation, since all models are fitted with a drainage cock at the rear. Position the drain, turn the rotary knob on the side and hey presto!

A further, particularly practical small highlight: the optional lid can be transformed into a drainage tray. Simply invert the lid. The collected fluid can therefore be reused in the trough.

It doesn't matter whether you use ultrasound occasionally or constantly for cleaning. The Basic-Clean devices offer a modern design, efficiency and "Made in Germany" quality. They set the new standard of cleaning at JOKE®.



All Basic-Clean models at a glance

Technical data	Basic-Clean 80 H	Basic-Clean 175 H	Basic-Clean 275 H	Basic-Clean 425 H	Basic-Clean 575 H	Basic-Clean 690 H	Basic-Clean 940 H	Basic-Clean 950 H	Basic-Clean 1275 H	Basic-Clean 1800 H	Basic-Clean 2800 H	Basic-Clean 4500 H	Basic-Clean 9000 H
Total volume	0,80 litre	1.75 litre	2.75 litre	4.25 litre	5.75 litre	6.90 Liter	9.40 litre	9.50 litre	12.75 litre	18 litre	28 litre	45 litre	90 litre
Trough, outside dimensions (W x D x H)	190x85x60 mm	151x137x100 mm	240x137x100 mm	240x137x150 mm	300x151x150 mm	505x137x100 mm	505x137x150 mm	300x240x150 mm	300x240x200 mm	327x300x200 mm	505x300x200 mm	500x300x300 mm	600x500x300 mm
Device, outside dimensions (W x D x H)	206x116x178 mm	175x180x212 mm	300x179x214 mm	300x179x264 mm	365x186x264 mm	568x179x214 mm	568x179x264 mm	365x278x264 mm	365x278x321 mm	390x340x321 mm	568x340x321 mm	615x370x467 mm	715x570x467 mm
Supply voltage	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz	240 V, 50/60 Hz
Weight	2.0 kg	2.1 kg	3.3 kg	4.0 kg	5.1 kg	5.6 kg	6.4 kg	5.9 kg	7.5 kg	8.5 kg	11.0 kg	25.0 kg	38.0 kg
Ultrasonic frequency	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz	37 kHz
Ultrasonic peak power	240 W	280 W	320 W	560 W	600 W	600 W	600 W	600 W	800 W	800 W	1200 W	1600 W	3200 W
Heater	60 W	60 W	200 W	200 W	400 W	600 W	600 W	400 W	800 W	800 W	1200 W	1600 W	2000 W
Total power consumption	90 W	95 W	280 W	340 W	550 W	750 W	750 W	550 W	1000 W	1000 W	1500 W	2000 W	2800 W
Sweep function	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
DeGas / Auto-DeGas	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Handles	-	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Drain / diameter (inch)	-	-	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"

All Basic-Clean Models are also available without heating system